

PETRON BLAZE RACING SYNTHETIC BLEND 10W-40

DESCRIPTION

Product Data Sheet

Petron Blaze Racing Synthetic Blend 10W-40 with TS³ is a multi-grade semi-synthetic engine oil designed to provide maximum engine protection for all passenger cars and light-duty trucks and vans powered by gasoline engines. Blaze Racing Synthetic Blend 10W-40 is suitable for high-performance engines, especially those fitted with turbochargers, or operated under the most severe conditions.

The Thermal Stress Stabilizing System (TS³) keeps the oil stable even at extreme temperatures, providing ultimate protection from engine stress.

GRADE

• SAE 10W-40

APPLICATION

 Gasoline-powered cars/trucks, high speed automotive engines

TYPICAL CHARACTERISTICS

Specific Gravity at 15.6°C Flash Point, COC, °C Color, ASTM Kinematic Viscosity at 40°C, cSt Kinematic Viscosity at 100°C, cSt Viscosity Index TBN (mg KOH/g)

PROPERTIES

- Longer oil drain interval
- Lower tailpipe emissions
- Better thermal stability and oxidation resistance
- Better volatility and viscosity properties
- Better wear protection
- Better engine sludge and soot control
- Reduced vehicle maintenance cost

QUALITY LEVELS

It meets the requirements of:

- API SN/CF
- ACEA A3/B4-12
- MB-Approval 229.1

AVAILABLE PACKAGES

- 6 x 4 liters in carton
- 24 x 1 liter in carton

0.8752

230

2.5

98.22

14.35

151

9.5