



PETRON REV-X MULTIGRADE HD4X SAE 15W-40

DESCRIPTION

PETRON REV-X MULTIGRADE HD4X SAE 15W-40 with DC Tech is a high performance multi-grade engine oil designed to provide ultimate protection to heavy-duty diesel vehicles requiring an API CF quality level.

Dynamic Cleaning Technology (DC Tech) is an advanced multi-functional additive system that promotes engine cleanliness for more efficient operation and longer engine life.

PERFORMANCE BENEFITS

- It provides optimal defense against acid attack and corrosion when subjected to high temperature and engine stress
- It gives first-rate protection against formation of gums and varnish due to its high oxidation and thermal stability
- It provides exceptional wear protection on critically loaded components for longer engine life

GRADE

SAE 15W-40

TYPICAL CHARACTERISTICS*

Color, ASTM	L1.5
Density at 15°C, kg/L	0.8816
Kinematic Viscosity at 40°C, cSt	107.9
Kinematic Viscosity at 100°C, cSt	14.38
Viscosity Index	136
Flash Point, COC, °C	236
TBN, mg KOH/g	10.2

** Only typical results and may vary per production blend*

APPLICATIONS

- Diesel-fed vehicles requiring an API CF quality.
- Mixed fleets of automotive diesel vehicles such as FX, trucks, and busses.
- Off-road vehicles, agricultural tractors, and equipment.

INDUSTRY & OEM SPECIFICATIONS

- It has the performance profile of:
 - API CF/SF
 - MB-Approval 227.1

AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.