



Product Data Sheet

PETRON SPRINT 4T SR450 PREMIUM MULTIGRADE SAE 20W-50

DESCRIPTION

PETRON SPRINT 4T SR450 PREMIUM MULTIGRADE SAE 20W-50 with TCS is a high quality motorcycle engine oil suitable for use in both air-cooled and liquid-cooled four-stroke motorcycles.

Thermal Control System (TCS) is an advanced additive technology that enhances the oil's thermal endurance, volatility profile, and oxidation stability.

PERFORMANCE BENEFITS

- Excellent wear protection for longer engine life
- Excellent shear stability to resist oil thinning and breakdown
- Outstanding detergency to provide extended protection and superior engine cleanliness
- Optimum friction characteristics for good clutch engagement

GRADE

SAE 20W-50

APPLICATION

- For air-cooled and liquid-cooled 4-stroke motorcycles

INDUSTRY & OEM SPECIFICATIONS

- It has the performance profile of:
 - JASO MA/MA2
 - API SL

AVAILABLE PACKAGE

Please contact our Sales Team for the available packages.

TYPICAL CHARACTERISTICS*

Color, ASTM	L2.0
Density at 15°C, kg/L	0.8714
Kinematic Viscosity at 40°C, cSt	145.6
Kinematic Viscosity at 100°C, cSt	17.85
Viscosity Index	136
Flash Point, COC, °C	246

** Only typical results and may vary per production blend*