

Product Data Sheet PETRON SPRINT 4T SR800 FULLY SYNTHETIC

SAE 10W-40

DESCRIPTION

PETRON SPRINT 4T SR800 FULLY SYNTHETIC SAE 10W-40 with TCS is a toptier, engine oil formulated to provide outstanding protection for modern, high performance motorcycle under extreme driving conditions. It is suitable for use in both air-cooled and liquid-cooled four-stroke motorcycles.

Thermal Control System (TCS) is an advanced additive technology that enhances the oil's thermal endurance, volatility profile, and oxidation stability.

PERFORMANCE BENEFITS

- Excellent friction characteristics for optimum wet clutch performance
- Superior shear stability to prevent oil breakdown even at high temperature and extreme operating conditions
- Outstanding detergency to provide extended protection and superior engine cleanliness
- Exceptional thermal stability to prevent oil thickening and piston deposits under high-temperature conditions

GRADE

SAE 10W-40

TYPICAL CHARACTERISTICS*

Color, ASTM Density at 15°C, kg/L Kinematic Viscosity at 40°C, cSt Kinematic Viscosity at 100°C, cSt Viscosity Index Flash Point, COC, °C

* Only typical results and may vary per production blend

APPLICATION

• Four-stroke motorcycle engines

INDUSTRY & OEM SPECIFICATIONS

- It has the performance profile of:
 - JASO MA / MA2
 - API SM

AVAILABLE PACKAGES

L2.0

0.8561

96.26

14.58

157

238

Please contact our Sales Team for the available packages.

For inquiries, contact **PETRON CORPORATION,** Jesus St., Pandacan, Manila 1011, Philippines Tel. No. (632) 8-884-9200