



Product Data Sheet

PETRON REV-X FULLY SYNTHETIC 5W-30

DESCRIPTION

PETRON REV-X FULLY SYNTHETIC SAE 5W-30 is a high performance fully synthetic diesel engine oil formulated with high quality base oils and additive package designed to deliver superior performance on wear protection, deposit control, soot-related viscosity control and fuel economy benefits for modern heavy duty diesel vehicles.

PROPERTIES

- Provides outstanding wear protection performance and oil consumption control.
- Provides improved fuel economy and low temperature performance over conventional oils.
- Provides protection from thermal and oxidative breakdown.
- Demonstrates ability to extend oil drains.

GRADE

- SAE 5W-30

APPLICATIONS

- Turbocharged or supercharged high performance heavy duty diesel engines under both low speed-high speed and high speed-high load conditions.
- Light duty trucks
- Gasoline engines requiring an API SN lubricating performance

QUALITY LEVELS

- It has the performance profile of:
 - API CJ-4
 - API SN
 - ACEA E9
 - Cummins CES 20081
 - DFS 93K218
 - MAN M 3575
 - MB 228.31
 - MTU Oil Category 2.1
 - Volvo VDS-4/ Mack EO-O Premium Plus/ Renault RLD-3

AVAILABLE PACKAGES

Please contact our Sales Representative for the available packages.

TYPICAL CHARACTERISTICS*

Density at 15 °C, kg/L	0.8556
Flash Point, COC, °C	218
Color, ASTM	L4.0
Kinematic Viscosity at 40°C, cSt	72.46
Kinematic Viscosity at 100°C, cSt	11.94
Viscosity Index	161
TBN, mg KOH/g	10.8

**Only typical properties and may vary per production blend*