



## Product Data Sheet

# PETRON SPRINT 4T SR400 PREMIUM MULTIGRADE SAE 15W-40

### DESCRIPTION

**PETRON SPRINT 4T SR400 PREMIUM MULTIGRADE SAE 15W-40** with TCS is high quality motorcycle engine oil suitable for use in both air-cooled and liquid-cooled four-stroke motorcycles.

Thermal Control System (TCS) is an advanced additive technology that enhances the oil's thermal endurance, volatility profile, and oxidation stability.

### PERFORMANCE BENEFITS

- Excellent wear protection for longer engine life
- Excellent shear stability to resist oil thinning and breakdown
- Outstanding detergency to provide extended protection and superior engine cleanliness
- Optimum friction characteristics for good clutch engagement

### GRADE

SAE 15W-40

### APPLICATION

- Four-stroke motorcycle engines

### INDUSTRY & OEM SPECIFICATIONS

- It has the performance profile of:
  - JASO MA/MA2
  - API SL

### AVAILABLE PACKAGE

Please contact our Sales Team for the available packages.

### TYPICAL CHARACTERISTICS\*

Color, ASTM	L1.5
Density at 15 °C, kg/L	0.8677
Kinematic Viscosity at 40°C, cSt	103.8
Kinematic Viscosity at 100°C, cSt	14.04
Viscosity Index	137
Flash Point, COC, °C	240

*\* Only typical results and may vary per production blend*